

- Öffnen Sie nicht das Sensorgehäuse.
- Ziehen oder schlingen Sie das Messseil nicht um ungeschützte Körperteile.
- Ziehen Sie das Messseil nicht über den angegebenen Messbereich heraus.
- Lassen Sie das Messseil nicht schnappen.
- > Verletzungsgefahr
- Beschädigen Sie nicht das Messseil.
- Ölen oder fetten Sie das Messseil nicht.
- Knicken Sie das Messseil nicht.
- Ziehen Sie das Messseil nicht schräg.
- Lassen Sie das Messseil nicht um Objekte schleifen.
- Befestigen Sie das Messseil eingezogen am Messobjekt.
- > Beschädigung oder Zerstörung des Sensors

- Montage durch Montagebohrungen für 3 Schrauben M6 oder
- Montage durch beiliegende 4 Nutensteine M6

- i** Bevorzugen Sie nach Möglichkeit eine Einbaulage mit Messeilaustritt nach unten. Dies verhindert, dass Flüssigkeiten in den Messeilaustritt eindringen können.

- Schutzart: Abhängig vom Encoder
- Temperaturbereich
 - Betrieb: -40 ... +85 °C
 - Lagerung: -40 ... +85 °C
- Luftfeuchtigkeit: 5 ... 95 % RH (nicht kondensierend)
- Umgebungsdruck: Atmosphärendruck
- Vibration: Entsprechend DIN EN 60068-2-6
- Mechanischer Schock: Entsprechend DIN EN 60068-2-27

- 1 Sensor
4 Nutzensteine M6
1 Synchroflansch-Adapter mit Montagematerial
1 Montageanleitung

Befestigung und maximaler Schrägzug des Messseils

Maßzeichnung Serien WPS-3500-K100-M / WPS-5000-K100-M /
WPS-8000-K100-M, Abmessungen in mm

MICRO-EPSILON MESSTECHNIK GmbH & Co. KG
Koenigbacher Str. 15 • 94469 Ortenburg / Germany
Tel. +49 8542 / 168-0 • Fax +49 8542 / 168-90
info@micro-epsilon.com • www.micro-epsilon.com
Your local contact: www.micro-epsilon.com/contact/worldwide/
X977X479-B012115TSw

- ➡ Montieren Sie den Flansch am Encoder (Drehgeber).
- ➡ Stecken Sie die Welle des Encoders in die Welle der Seilzug-Mechanik.
- ➡ Drehen Sie den Encoder bis die Madenschraube an der Seilzug-Mechanik in einer Linie zu einer der vier Löcher im Flansch steht. Ziehen Sie die Madenschraube über das entsprechende Loch im Flansch mit 0,6 Nm an.
- ➡ Montieren Sie die Gruppe Encoder/Flansch an der Seilzug-Mechanik.
- Achten Sie darauf, dass das Messseil immer durch den Federmotor gespannt ist, um ein Abspringen von der Seiltrommel zu vermeiden.
- Beachten Sie die Hinweise des Encoder-Herstellers.

Montage von Synchroflansch-Adapter und Encoder, WPS-1500-K100-M / WPS-2500-K100-M

Montage von Synchroflansch-Adapter und Encoder, WPS-3500-K100-M / WPS-5000-K100-M/WPS-8000-K100-M

Dipl.-Ing.(FH) Eduard Huber, MBA
Leiter Qualitätsmanagement

Serie WPS, Mechaniken
WPS series, mechanism
K100, K140



Warnings

- Do not open the sensor housing.
- Do not pull or loop the measuring wire around unprotected parts of the body.
- Do not pull out the measuring wire beyond the measuring range indicated.
- Do not let the measuring wire snap.
- > Risk of injury
- Do not damage the measuring wire.
- Do not oil or grease the measuring wire.
- Do not kink the measuring wire.
- Do not pull the measuring wire diagonally.
- Do not let the measuring wire drag around objects.
- Attach the measuring wire to the measured object while the wire is retracted.
- > Damage to or destruction of the sensor

Sensor Mounting

- ➡ Mount the sensors as follows:
 - Mounting through mounting holes for 3x M6 screws or
 - the 4x M6 slot nuts included.

The sensor does not have to be oriented in a special way.

- ➡ Select the installation position in such a way that damage to or contamination of the measuring wire is avoided.

- If possible, prefer an installation position in which the measuring wire exits downward. This prevents liquids from entering the measuring wire outlet.

Proper Environment

- | | |
|----------------------|----------------------------------|
| - Protection class: | Depending on encoder |
| - Temperature range: | |
| ▪ Operation: | -40 ... +85 °C (-40 ... +185 °F) |
| ▪ Storage: | -40 ... +85 °C (-40 ... +185 °F) |
| - Humidity: | 5 ... 95 % RH (non-condensing) |
| - Ambient pressure: | Atmospheric pressure |
| - Vibration: | According to DIN EN 60068-2-6 |
| - Mechanical shock: | According to DIN EN 60068-2-27 |


Unpacking, Included in Delivery

- 1 Sensor
- 4 Slot nuts M6
- 1 Synchro flange adapter with mounting materials
- 1 Assembly Instructions

Guiding and Attaching the Wire

If the measuring wire must be pulled out of the sensor to guide the wire or attach it to the measured object:

- the sensor must not be held by a second person during that process,
- the measuring wire must not be pulled out beyond the measuring range listed,
- the area around the sensor must be protected against snapping of the measuring wire.




- ➡ Fix the measuring wire to the target using a wire clip.
- ➡ Guide the measuring wire vertically out of the sensor housing.

Diagonal pull is only permitted up to 3 degrees.


If you drag the measuring wire over the insertion hole or other objects, the measuring wire will be damaged and/or tear.

- If the measuring wire cannot be fed vertically out of the housing, it is essential to use a guide pulley, also see Optional Accessories in the Appendix of the Operating Instructions.


- ➡ Guide the measuring wire in a protected area so that it cannot get caught or otherwise be damaged.




Dimensional Drawings



Dimensional drawing of WPS-1500-K100-M / WPS-2500-K100-M, dimensions in mm (inches, rounded off)



Dimensional drawing of WPS-3500-K100-M / WPS-5000-K100-M / WPS-8000-K100-M, dimensions in mm (inches, rounded off)



Dimensional drawing of WPS-12000-K140-M dimensions in mm (inches, rounded off)


You can find more information about the sensor in the operating instructions. They are available online at: <https://www.micro-epsilon.com/download-file/man--wireSENSOR-WPS-K100-M--en.pdf>



Installing the Encoder


- ➡ Mount the flange on the encoder (rotary encoder).
- ➡ Insert the shaft of the encoder into the shaft of the draw-wire mechanism.
- ➡ Turn the encoder until the set screw on the cable pull mechanism is in line with one of the four holes in the flange. Tighten the set screw over the corresponding hole in the flange to 0.6 Nm.
- ➡ Mount the encoder/flange assembly on the draw-wire mechanism.
- Make sure that the measuring wire is always tensioned by the spring motor in order to prevent it from jumping off the cable drum.
- Observe the installation instructions issued by the manufacturer of the encoder.

WPS-1500-K100-M / WPS-2500-K100-M Models



Mounting the synchro flange adapter and encoder, WPS-1500-K100-M / WPS-2500-K100-M

WPS-3500-K100-M / WPS-5000-K100-M / WPS-8000-K100-M Models



Mounting the synchro flange adapter and encoder, WPS-3500-K100-M / WPS-5000-K100-M / WPS-8000-K100-M

Declaration of incorporation

Declaration of Incorporation of Partly Completed Machinery according to The Supply of Machinery (Safety) Regulations 2008, No. 1597 Annex II B
The manufacturer and person authorised to compile the relevant technical documentation

MICRO-EPSILON MESSTECHNIK GmbH & Co. KG
Königbacher Straße 15, 94496 Ortenburg / Germany
hereby declare that the machine designated below complies with the essential health and safety requirements of the Supply of Machinery (Safety) Regulations 2008, No. 1597, including modifications to it applicable at the time of this declaration, based on its design and construction and in the version put on the market by us – to the extent that the scope of supply allows.

Machine design: Draw-wire sensor (mechanics and models with potentiometer output)

Type designation: WDS-xxx, WPS-xxx

The following essential health and safety requirements according Annex II of o.g. regulation are applied and fulfilled:

- Nr. 1.1.2 “Principles of safety integration”
- Nr. 1.7.3 “Marking of machinery”
- Nr. 1.7.4 “Instruction”

Furthermore, we declare compliance with the following directives and standards including the modifications applicable at the time this declaration is made:

- SI 2008 No. 1597: The Supply of Machinery (Safety) Regulations 2008
 - EN ISO 13857:2019 Safety of machinery - Safety distances to prevent hazard zones being reached by upper and lower limbs
- SI 2012 No. 3032: The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012
 - EN IEC 63000:2018 Technical documentation for the assessment of electrical and electronic products with respect to the restriction of hazardous substances

We also declare that the special technical documentation for this partially completed machine has been created in accordance with Annex VII, Part B, and commit ourselves to disclose this to the market surveillance authorities upon request.

The partly completed machinery must not be put into service until the final machinery into which it is to be incorporated has been declared in conformity with the provisions of the Directive, where appropriate.

Ortenburg, Germany
June 21, 2023

Dipl.-Ing.(FH) Eduard Huber, MBA
Quality Manager

Declaration of Incorporation

Declaration of incorporation according to EC Machinery Directive 2006/42/EC, Annex II B

The manufacturer and person authorized to compile the relevant technical documents

MICRO-EPSILON MESSTECHNIK GmbH & Co. KG
Königbacher Straße 15, 94496 Ortenburg / Germany

hereby declare that the machine designated below complies with the relevant fundamental health and safety requirements of the EC Machinery Directive, including modifications to it applicable at the time of this declaration, based on its design and construction and in the version put on the market by us – to the extent that the scope of supply allows.

Machine design: Draw-wire sensor (mechanics and models with potentiometer output)
Type designation: WDS-xxx, WPS-xxx

The following fundamental health and safety requirements according to Annex I of the directive specified above have been applied and complied with:

- No. 1.1.2. Principles of safety integration
- No. 1.7.3. Marking of machinery
- No. 1.7.4. Operating instructions

Furthermore, we declare compliance with the following directives and standards including the modifications applicable at the time this declaration is made:

- Directive 2006/42/EC (machinery)
 - EN ISO 13857:2019 Safety of machinery - Safety distances to prevent hazard zones being reached by upper and lower limbs
 - EN 60204-1:2018 Safety of machinery - Electrical equipment of machines - Part 1: General requirements
- Directive 2011/65/EU (RoHS)
 - EN IEC 63000:2018 Technical documentation for the assessment of electrical and electronic devices with respect to the restriction of hazardous substances

We also declare that the special technical documentation for this partially completed machine has been created in accordance with Annex VII, Part B, and commit ourselves to disclose this to the market surveillance authorities upon request. The commissioning of these partially completed machines is prohibited until the partially completed machine(s) has/have been installed in a machine that meets the requirements of the EC Machinery Directive and for which an EU Declaration of Conformity according to Annex II, Part A exists.

Ortenburg, Germany
July 1, 2021

Dipl.-Ing.(FH) Eduard Huber, MBA
Quality Manager